

ΕΚΛΟΓΗ ΚΑΛΩΔΙΩΝ / ELECTRIC CABLE SELECTION
ΕΚΚΙΝΗΣΗ ΑΣΤΕΡΑ - ΤΡΙΓΩΝΟ / STAR - DELTA CONNECTION

ΙΣΧΥΣ / VOLT 380 V		ΔΙΑΤΟΜΗ ΚΑΛΩΔΙΩΝ / CABLE X- SECTION 2 x NYY (3 xmm ²)												ΠΑΡΑΛΛΗΛΑ ΚΑΛΩΔΙΑ / PARALLEL CABLES x...mm ² 6					
		2,5	4	6	10	16	25	35	50	70	95	120	150	35	50	70	95	120	150
4	3	230	370																
5,5	4	170	270	400															
7,5	5,5	120	200	300	500														
10	7,5	90	150	220	380														
13	9,2	70	120	180	310	490													
15	11	60	100	150	260	400													
20	15	50	80	110	200	310	490												
25	18,5		60	90	160	250	400	560											
30	22		50	70	130	210	340	470											
35	26		45	68	110	180	290	410											
40	30			60	100	160	250	360	500										
50	37			40	80	130	200	290	410										
60	45				70	100	170	240	350	480				480					
75	55					80	130	180	260	360	500			360	520				
90	66						110	160	230	320	450	520		320	460				
100	75						100	150	200	290	380	440	540	290	400	580			
125	90							120	170	230	300	370	450	230	340	460	600		
150	110							100	140	200	250	300	370	200	280	400	500	600	
180	132								120	165	210	260	310	165	240	330	420	520	
200	150									150	190	230	280	150	200	260	380	460	560
225	165									130	170	200	240	130	180	220	340	400	480
250	185									125	160	190	230	125	170	210	320	380	460
275	200										140	170	200		150	180	280	340	400

Οι παραπάνω τιμές αναφέρονται σε πτώση τάσης 3% και θερμοκρασία 25 β. κελσίου

The above figures, are valid for 3% voltage drop and temperature up to 25 degrees Celcius.