

No.	Description		Stainless Steel Option	Standard Material
1	Discharge Head		Stainless — Type AISI 416 or 420 or 316 or 304 (depends on the needs)	Cast Iron GG25 or GG40, DIN
	Oil Can		Stainless — Type AISI 416 or 420 or 316 or 304 (depends on the needs)	Cast Iron GG25 or GG40, DIN
2	Head Shaft		Stainless Steel AISI 316L or 304L	Stainless Steel ASTM 420
	Spindle Assembly	Product Lub.	Stainless Steel AISI 316L or 304L	Cast Iron GG25 or GG40, DIN
3	Adjusting Nut		Stainless Steel AISI 316L or 304L	Mild Steel
4	Stuffing Box	Product Lub.	Stainless Steel AISI 316L or 304L	Cast Iron — GG45
5	Stuffing Box Busing	Product Lub.	Stainless Steel AISI 316L or 304L	Bronze —Federalloy III
6	Bearings			Standard Commerce Material
7	Output Flange		Stainless Steel AISI 316L or 304L	Cast Iron GG25 or GG40, DIN
8	Column Pipe	Product Lub.	Stainless Steel AISI 316L or 304L	Pipe — ASTM
9	Column Coupling	Product Lub.	Stainless Steel AISI 316L or 304L	Pipe — ASTM A53
10	Throttle Bushing	Product Lub.	Stainless Steel AISI 316L or 304L	Cast Iron GG25 or GG40, DIN
11	Lineshaft	W/L — Stainless	Stainless Steel AISI 316L or 304L	Stainless Steel AISI 420
12	Lineshaft Coupling	Product Lub.	Stainless Steel AISI 316L or 304L	
13	Water Lube Retainer	Product Lub.	Stainless Steel AISI 316L or 304L	Bronze
14	Suction Flange		Stainless Steel AISI 316L or 304L	Cast Iron GG25 or GG40, DIN
15	Discharge Bowl	Product Lub.	Stainless Steel AISI 316L or 304L	Cast Iron — GG25 - GG35 - GG40
16	Foot Valve	Product Lub.	Stainless Steel AISI 316L or 304L	Cast Iron GG25 – GG 35 – GG40
17	Intermediate Bowl		Stainless Steel AISI 316L or 304L	Cast Iron GG25 – GG35 – GG45
18	Top Inter Bowl		Stainless Steel AISI 316L or 304L	Cast Iron GG25 – GG35 – GG45
19	Impeller		Stainless Steel AISI 316L or 304L	Phosphatic Bronze Impeller.
20	Suction Bowl		Stainless Steel AISI 316L or 304L	Cast Iron GG25 – GG35 – GG45
21	Suction Strainer		Stainless Steel AISI 316L or 304L	Mild Steel
22	Bowl Shaft		Stainless Steel AISI 316L or 304L	Stainless Steel ASTM 420
23	Hex Bolt		Stainless Steel AISI 316L or 304L	Steel — SAEJ 429, Gr. 8
24	Lubrication Pipe on the Oil Can Assembly		Stainless Steel AISI 316L or 304L	Mild Steel Pipe ½" or 1 O"
25	Hex Bolts on the Oil Can Assembly and the Spindle Assembly		Stainless Steel AISI 316L or 304L	Standard Commerce Material , Galvanized steel.